

Sutphen Rear Mount Aerial Ladder (SLR) Project

Start December 2014

Sutphen Rear Mount Aerial Ladder (SLR) Project

Start December 2014

SLR75

HS-5587 Demo 404

(Eden, NC)

- First build
- Double high split depth body
- Full depth main hose bed
- Sliding tool board and stokes box
- Large L1 and R1 compartments
- 3 single stack crosslays
- Lots of compartment space



How do we improve?



- Recess rear access ladder
- More hose storage options
- Easier access to dunnage area equipment
- Need to increase rear suspension GAWR
- Eliminate slam door over outriggers
- Hydraulic tank is difficult to install and service
- Simplify hydraulic system and reduce the number of parts
- Add service access to hydraulic and electrical components in body

HS-5901 Demo 429

(Elkhart, IN)

- Second Build
- Side Stacker hose bed
- Full depth L1 compartment
- Aerial access ladder recessed in body
- Service access panel on rear of body
- 8" tailboard for pike pole accessibility
- Easier rear tow eye access
- Compartments over wheel well for long handle tools
- 35K rear suspension
- Bolt on dunnage panels for cord reel and generator access.
- Hydraulic tank moved inside of cradle utilizing unused space.
- Simplified water tank
- New multiple function hydraulic combination block (Boat Anchor)







HS-5964 Pinellas Park, FL


- First Customer Spec. Build
- New pump module dunnage options
 - Deadlay hose
 - Scoop stretcher
 - Backboard
- Waterous pump
- 73" cab
- Cord reel mounted in rear of body
- Storage compartment above cord reel
- 3 Position Aerial Intercom



HS-6007 Painesville, OH

- Currently under construction
- Similar dunnage area as Pinellas Park
- Storage compartment at rear of body
- Double high split depth body
- Custom hose bed configuration
- Rear discharge in main hosebed







How do we improve?

- Move outrigger hydraulic hoses inside of jack tubes
- Lower L1 and R1 body height to eliminate door roll issues with very tall door
- Move pike poles down low outboard of frame rails increasing compartment volume
- Develop fixed rear access ladder with easy installation and removal for service access
- More space is needed between turntable and body.
- Redesign turntable deck to be lighter and easier to install.
- Improve pedestal design for better service access and reduced manufacturing cost.
- New body design with ground ladders on the driver side and full width, side stacker hose bed on the officer side
- Improve hydraulic tank design and reduce volume
- Improve access to plumbing, tank fill and tank-to-pump connections
- Improve side-stacker body design to reduce manufacturing costs
- Establish standard locations for hydraulic components
- Establish standard body configurations for SQS2

HS-6118 Demo 438





RIGID E SERIES
30IN LED FLOOD LIGHT
1 EACH SIDE

RIGID D2 LED
BOOM SPOT LIGHTS
4 TOTAL

RIGID E SERIES
30IN LED FLOOD LIGHT
1 EACH SIDE

SUTPHEN

ELKHART COBRA E
(2) RIGID E2 20IN
LED DRIVING LIGHTS

R2

R1

WHELEN 500
LED

ELECTRIC OUTLETS

SMART POWER 10KW
HR GENERATOR

30 GALLON FOAM CELL
470 GALLON WATER TANK

850' TO 1,000' OF 5"
AND
750' TO 900' 3"


MANSERVER

WHELEN MCFLED
REAR BEACONS


HANNAY CORD REEL

3 CROSSLAYS


1.5IN DISCHARGE




L1 and R1 compartment shortened to be flush with rest of body. No pike poles in top of compartments







**New body design with
large officer side hose
bed. Full Depth R1.**




**Trombone style hydraulic lines
inside the outriggers.**








Modular option





SUTPHEN





Sub-Frame shown in yellow
Added before the body

**Improved deck frame
design with improved
handrail attachment.**





Better way of attaching the deck to the upper assembly.



Sutphen Rear Mount Aerial Ladder (SLR) Project

SLR108


Start May 2016

Pro's


1. Compartment Volume
 - a. Transverse Compartment
 - b. 8 air bottles
 - c. Fans, Stokes, Rescue Tools, etc...
2. Water Capacity (500 gallons)
3. Hose Capacity (up to 1400' of 5"
or 900' of 5" & 250' of 2 ½")
4. Narrow Jack Span (under 16')
5. 4000 pounds of equipment
6. Same pump module as SLR75

Concerns

1. Weight distribution
 - a. Will ISX require 25.5k front axle?
 - b. Thin margin with ISL
2. Access to turntable?
3. Cost to build
4. Travel Height ~ 12'
5. Aerial Waterway Flow
6. Tank Flow
7. Vehicle in service weight
8. Stability at rated load




298 cu ft
Total



Body Length Options


Short

Ground ladders full width of pump module. Limiting crosslays.




Medium


Ground ladders half width of pump module. Allowing full crosslays.



Long

Ground ladders behind pump module. Allowing full crosslays and more plumbing options.








1400' of 5"
Or
900' of 5" & 250' of 2 1/2"


35' 2-section
(2) 16' roof
24' 3-section
14' combination


Pike Poles/Fire Hooks














236	Wheelbase (inches)
4000	Equipment Allowance (pounds)
500	Water Capacity (gallons)
23000	Front Axle Capacity (pounds)
46000	Rear Axle Capacity (pounds)


ISX 500 hp engine			ISL 450 hp engine	
Loaded	Unloaded*		Loaded	Unloaded*
23572.44	21842.87	Front	21784.59	19798.94
42677.03	32794.60	Rear	43114.88	34838.53
66249.47	54637.47	Total	64899.47	54637.47


* (including ground ladders, no water, no hose, no personnel, no equipment)














4th Section Extension Cables: 8mm Dynaflex
Sheaves vertical


3rd Section Extension Cables: 3/8" Apex
Sheaves angled

Fourth Section: 27.5"w x 15.6"h

Third Section: 30.8"w x 18.7"h

Second Section: 34.25"w x 21.9"h

First Section: 38.6"w x 24.6"h





Finished Chassis

P
u
m
p

M
o
d
u
l
e



Rear Body Support Frame



Front Body Support Drops






Rear of Body



A1
"Hydraulic
Compartment"







Strain Gauge Tests



5° Slope Test



1.5 x Rated Load
Overturning Test





Aerial Waterway Flow Test

Goal set at
1500 gpm
~~at~~
Full Elevation
Full Extension

1136 gpm, with 3" valve, 20' of
supply line

We have not tested with the
rear inlet, nor 4" discharge valve



Pro's

1. Compartment Volume – **early feedback tells us that the tall compartments are too tall/inaccessible.**
 - a. Transverse Compartment
 - b. 8 air bottles
 - c. Fans, Stokes, Rescue Tools, etc...
2. Water Capacity (500 gallons)
3. Hose Capacity (up to 1400' of 5" or 900' of 5" & 250' of 2 ½")
- ~~4. Narrow Jack Span (under 16')~~
5. 4000 pounds of equipment
6. Same pump module as SLR75

Concerns

1. Weight distribution
 - a. Will ISX require 25.5k front axle?
 - b. Thin margin with ISL
2. Access to turntable? **Need feedback.**
3. Cost to build – **always working on this**
4. Travel Height ~ 12'
5. Aerial Waterway Flow – **tested at East**
6. Tank Flow – **500 gallons**
7. Vehicle in service weight - ???
8. Stability at rated load – **wide stance down jacks at rear**

Solutions

1. Redesign aerial to reduce weight
2. Move rear jacks toward outside and rear of body


More Drastic Changes

1. Torque tube redesign to allow ground ladders to be stowed on beam

Body Length Options


Short

Ground ladders full width of pump module. Limiting crosslays.




Medium


Ground ladders half width of pump module. Allowing full crosslays.




Long

Ground ladders behind pump module. Allowing full crosslays and more plumbing options.









SUTPHEN

Beyond!



Thank You!