

Features	SLR108
Base Price	
Stabilizers	2 sets of underslung
Stabilizer Spread	16'
Platform Size	N/A
Rear Axle	Tandem
Hosebed Capacity	1,000' of 5"
Crosslay Capacity	(2) 200' of 1.75" each Optional 3rd Crosslay
Crosslay length	74"
Pump Module Width	39"
Pump Module Height	46.25"
Ladder Wind & Ice Rating	30 mph sustained 50 mph gusts 1/4" ice build-up
Ladder Compliment	Quint/Aerial/ISO
Aerial Vertical Reach	108'
Aerial Horizontal Reach	98' - 8.8"
Operating Envelope	75 to -5 degrees
Envelope Aerial Controls	Standard
Water Tank	Up to 500 Gallons
Water Pump Range	Hale Qmax/Qtwo 2,250 Wateous CSU/CMU 2,250
Ladder Tip Rating, Empty Waterway	750 lb
Ladder Tip Rating, Full Waterway	500 lb
Waterway Flow Capacity	1,000 gpm
Ladder Controls	Manual at Pedestal
Wheelbase (62" cab)	236"
Overall Length (12" Bumper, 62" Cab)	41' - 7.25"
Overall Height	~12'
Body Width	98"
CL of Rear Axle to Rear of Body	133.5"
Compartment Volume	Up to 239 cu. Ft.
Body Material	304 Stainless Steel
GVWR Front	23,000 lbs
GVWR Rear	48,000 lbs (300 gal. water) 52,000 lbs (400 & 500 gal. water)
Ladder Fly Section Inside Width	27.5"
Ladder Fly Section Inside Height	15.625"
Stablizer Short Jack	Yes
Stabilizer Controls	Electric w/Manual Backup