



PRO ONE GREASE APPLICATION

OVERVIEW

The Sales Department would like to inform the dealer network that the use of Pro One EP-2 grease has now been approved for use on Sutphen products. Please refer to the details below on this particular product application.

- Pro One is approved for all chassis applications requiring grease.
- Pro One is approved for all Dublin applications for chassis and aerials requiring grease.
- Pro One is approved for Hilliard chassis applications only. This product has not been validated on the boom, but there is plans to do so in the future. At this time the only grease approved for Hilliard Aerial devices is Prizm.

For those of you not familiar with Pro One grease. A product bulletin has been attached for reference. You may also visit their website for more info at <https://www.pro1energy.com/products/rig-maintenance/ep-2-multipurpose-grease/>.

Ordering process: The attached warehouse order form is for smaller orders under \$600. The attached Drop Ship order form comes from our manufacturer and are ordered by the case only and usually sent on pallets. Please note there is a price break on the Drop ship orders.

Delivery Terms/Times: All orders will be sent to the warehouse or Mfg the day they are submitted.

Payment Terms/Methods: An invoice will be sent once the item has arrived to you or the customer. Request for payment must be completed in 3 weeks on warehouse items once they have been received. For the drop ship items, Pro One is requesting 50% upfront and 30 days for the balance after the items have been received. They will take credit cards, ACH Transfer, or check. All invoicing will be via e-mail.

Contact Information for Ordering:

Rich Walters
RichWalters3@gmail.com
1-614-216-7820

Paige Armstrong
parmstrong@pro-one.us
1-832-516-6700

Address: P.O. Box 4302
Williston, ND 58802

If you have any questions please feel free to reach out to engineering or your sales territory manager with any questions.

Created: 04/09/2019

By: J. Howell

Revised: 07/03/2019

EP-2 Industrial Grease

Extreme Pressure Performance from -40°F to 615°F!

Delivers outstanding extreme pressure protection to help maximize equipment life and performance, and help save energy, even under the harshest conditions. And with no harmful additives, this premium grease is environmentally friendly!



Approved by Ford TOX# 185984

REDUCE
FRICTION & HEAT



EXTEND
EQUIPMENT LIFE



SAVE THOUSANDS
IN MAINTENANCE
COSTS

TYPICAL PROPERTIES

NLGI Grade	2
Color	Blue
Thickener	Calcium Complex
Operating temperature range	-40°F to 615°F
Kinematic viscosity of base oils @40°C (ASTM 445)	216 cSt (1000 SUS)
Penetration @ 25°C (77°F) (ASTM D-217), mm/10	
Worked 60 strokes	270-295
Mechanical Stability (ASTM D-217) % change from P60	
P100,000 strokes	2.5%
P10,000 strokes with 50% H2O	<6.0%
Dropping Point (ASTM D-2265) °F (°C)	+572 (+300)
Oil Separation (ASTM D-1742) -24 hours @ 25°C (77°F)	0.17
Shell Roll Stability (ASTM D-1831)	<4.0%
Oxidation Stability (ASTM D-942) psi drop/500 hours	6.0 lbs
Oxidation Bearing Life (ASTM D-3527)	200 hours
4-Ball Wear Test (ASTM D-2266)	
mm scar, 40kg, 1200 RPM, 75°F, 1H	0.42mm
4-Ball EP test (ASTM D-2596) LWI, kg	>75
Weld Load, kgf	600
Timken OK Load (ASTM D-2509) lbs/kg	60/27
Rust test (ASTM D-1743)	Pass
Copper Corrosion test (ASTM D-130)	Pass/1b
Salt Fog Spray (ASTM B-117) hours to failure	>1000 hours
Water Washout (ASTM D-1264) @ 80°C, % loss	<2.5%
Wheel bearing leakage grams (ASTM D-1263)	
Modified @ 163°C (325°F)	0.4
Base Oil Characteristics	
Viscosity SUS @ 100°F	1100
Viscosity SUS @ 210°F	85
Pour Point, oF	+5
V.I. Min	95

ADVANTAGES:

- Extreme pressure protection
- Heavy load carrying capability
- Shear stability
- Oxidation resistant
- Corrosion resistant
- Reduces noise
- Reduces downtime
- Reduces power consumption
- Cling capability
- Seal compatibility

IDEAL FOR EQUIPMENT:

- Industrial
- Manufacturing
- Commercial
- Oil & Gas
- Marine
- Automotive
- Mining
- Construction
- Agriculture

ProOne#	Size	Case Pack
46014	14 oz./397g Cartridge	12
46035	35 lb./15.9 kg Pail	1
46120	120 lb./54.4 kg Keg	1
46400	400 lb./181.4 kg Drum	1

PRO ONE WAREHOUSE ORDER FORM

CUSTOMER:

Billing Address:

TO BE COMPLETED BY VENDOR

Order No: _____

Date: _____

Customer ID: _____

Telephone:

Ordering instructions: Email completed order form to
sales@globalgreenlubricants.com

Email:

SHIP/DELIVER TO:

Global Green Lubricants

2074 TAMARIN DR

COLUMBUS, OH 43235

sales@globalgreenlubricants.com

Telephone:

Email:

Payment Terms: Due on receipt

Freight Terms: FOB Warehouse

PRODUCT #	SIZE	PART DESCRIPTION	PRICE	ORDER QTY	LINE TOTAL
11012	12 oz.	Engine Life Treatment	\$28.26		\$0.00
11001	Gallon	Engine Life Treatment	\$103.19		\$0.00
13032	32 oz.	Heavy Duty Oil Stabilizer	\$20.36		\$0.00
13001	Gallon	Heavy Duty Oil Stabilizer	\$54.60		\$0.00
40004	4 oz. aerosol	XPL-101 Penetrating Lubricant	\$6.29		\$0.00
40012	12 oz. aerosol	XPL-101 Penetrating Lubricant	\$12.29		\$0.00
40022	22 oz. spray	XPL-101 Penetrating Lubricant	\$21.40		\$0.00
40001	Gallon	XPL-101 Penetrating Lubricant	\$73.20		\$0.00
41001	Gallon	Rust Pro Rust Inhibitor	\$72.60		\$0.00
12001	Gallon	Industrial Oil Concentrate	\$31.99		\$0.00
22001	Gallon	Hydraulic Treatment	\$87.59		\$0.00
46014	14 oz. Cartridge	EP-2 Grease*	\$12.29		\$0.00
47014	14 oz. Cartridge	Synthetic-EP-1 Grease**	\$17.30		\$0.00
32010	10 oz.	Fuel Maximizer	\$21.30		\$0.00
32001	Gallon	Fuel Maximizer	\$239.40		\$0.00
64001	Gallon	Waterless Wash & Shine	\$36.86		\$0.00

3% cash discount

SUBTOTAL

\$0.00

SALES TAX

SHIPPING

TOTAL

\$0.00

*NSF 142079 - Food Grade

**NSF142078 - Food Grade

Additional Notes:

Products based on availability

No minimum order

Alternate prices available for large orders

Note: Sales tax will be added to all orders
unless an exemption is on file

Prepared by:

Global Green Lubricants

2074 Tamarin Dr

Columbus, OH 43235

sales@globalgreenlubricants.com

Authorized by

Date

PRO ONE DROP SHIP ORDER FORM

CUSTOMER:

Billing Address:

Telephone:

Email:

TO BE COMPLETED BY VENDOR

Order No:

Date:

Customer ID:

Ordering instructions: Print completed order, sign e-mail with a legal e-signature

SHIP TO:

Telephone:

Email:

Global Green Lubricants
2074 Tamarin Dr.
Columbus, OH 43235

Email: sales@globalgreenlubricants.com

Payment Terms: 50% down / 50% at shipment
Freight Terms: FOB Warehouse

SHIPPING METHOD		SHIPPING INSTRUCTIONS				REQUESTED DELIVERY DATE	
PART NUMBER	SIZE	PART DESCRIPTION	QTY / CASE	DISCOUNTED FIELD PRICE / EA	DISCOUNTED FIELD CASE PRICE	CASE ORDER QTY	LINE TOTAL
11012	12 oz.	Engine Life Treatment	12	\$23.00	\$275.99		\$0.00
11001	Gallon	Engine Life Treatment	4	\$84.00	\$335.99		\$0.00
11005	5 Gallon Pail	Engine Life Treatment	1	\$345.99	\$345.99		\$0.00
11055	55 Gallon Drum	Engine Life Treatment	1	\$3,149.00	\$3,149.00		\$0.00
11275	275 Gallon Tote	Engine Life Treatment	1	\$15,745.00	\$15,745.00		\$0.00
13032	32 oz.	Heavy Duty Oil Stabilizer	6	\$16.97	\$101.80		\$0.00
13001	Gallon	Heavy Duty Oil Stabilizer	4	\$45.50	\$181.99		\$0.00
13005	5 Gallon Pail	Heavy Duty Oil Stabilizer	1	\$179.99	\$179.99		\$0.00
13055	55 Gallon Drum	Heavy Duty Oil Stabilizer	1	\$1,719.00	\$1,719.00		\$0.00
13275	275 Gallon Tote	Heavy Duty Oil Stabilizer	1	\$8,595.00	\$8,595.00		\$0.00
40004	4 oz. aerosol	XPL-101 Penetrating Lubricant	12	\$5.25	\$62.99		\$0.00
40012	12 oz. aerosol	XPL-101 Penetrating Lubricant	12	\$10.00	\$119.99		\$0.00
40022	22 oz. spray	XPL-101 Penetrating Lubricant	6	\$17.83	\$106.99		\$0.00
40001	Gallon	XPL-101 Penetrating Lubricant	4	\$61.00	\$243.99		\$0.00
40055	55 Gallon Drum	XPL-101 Penetrating Lubricant	1	\$2,414.00	\$2,414.00		\$0.00
41001	Gallon	Rust Pro Rust Inhibitor	4	\$60.50	\$241.99		\$0.00
41005	5 Gallon pail	Rust Pro Rust Inhibitor	1	\$302.99	\$302.99		\$0.00
41055	55 Gallon drum	Rust Pro Rust Inhibitor	1	\$3,324.00	\$3,324.00		\$0.00
12001	Gallon	Industrial Oil Concentrate	4	\$76.65	\$306.60		\$0.00
12005	5 Gallon Pail	Industrial Oil Concentrate	1	\$325.49	\$325.49		\$0.00
12055	55 Gallon Drum	Industrial Oil Concentrate	1	\$3,045.00	\$3,045.00		\$0.00
19001	Gallon	ACA Cutting Oil	4	\$49.50	\$197.99		\$0.00
19005	5 Gallon Pail	ACA Cutting Oil	1	\$207.99	\$207.99		\$0.00
19055	55 Gallon Drum	ACA Cutting Oil	1	\$2,079.00	\$2,079.00		\$0.00
22001	Gallon	Hydraulic Treatment	4	\$72.99	\$291.96		\$0.00
22005	5 Gallon Pail	Hydraulic Treatment	1	\$309.99	\$309.99		\$0.00
22055	55 Gallon Drum	Hydraulic Treatment	1	\$2,999.00	\$2,999.00		\$0.00
46014	14 oz. Cartridge	EP-2 Grease*	12	\$10.00	\$119.99		\$0.00
46035	35 lb. Pail	EP-2 Grease*	1	\$234.99	\$234.99		\$0.00
46120	120 lb. Pail	EP-2 Grease*	1	\$748.99	\$748.99		\$0.00
46400	400 lb. Drum	EP-2 Grease*	1	\$2,319.00	\$2,319.00		\$0.00
47014	14 oz. Cartridge	Synthetic-EP-1 Grease**	12	\$14.42	\$172.99		\$0.00
47035	35 lb. Pail	Synthetic-EP-1 Grease**	1	\$399.99	\$399.99		\$0.00
47120	120 lb. Pail	Synthetic-EP-1 Grease**	1	\$1,292.00	\$1,292.00		\$0.00
47400	400 lb. Drum	Synthetic-EP-1 Grease**	1	\$4,016.00	\$4,016.00		\$0.00
48014	14 oz. Cartridge	Lithium/Moly Grease	12	\$10.58	\$126.99		\$0.00
48035	35 lb. Pail	Lithium/Moly Grease	1	\$253.99	\$253.99		\$0.00
48120	120 lb. Pail	Lithium/Moly Grease	1	\$847.99	\$847.99		\$0.00
48400	400 lb. Drum	Lithium/Moly Grease	1	\$2,543.00	\$2,543.00		\$0.00
52035	35 lb. Pail	Wire Glide	1	\$148.99	\$148.99		\$0.00
52120	120 lb. Pail	Wire Glide	1	\$497.99	\$497.99		\$0.00
32016	10 oz.	Fuel Maximizer	12	\$15.00	\$179.99		\$0.00
32001	Gallon	Fuel Maximizer	4	\$130.00	\$519.99		\$0.00
32055	55 Gallon Drum	Fuel Maximizer	1	\$5,999.00	\$5,999.00		\$0.00

\$600 Minimum Order

Freight is TBD

SUBTOTAL	\$0.00
SALES TAX	
SHIPPING	
TOTAL	\$0.00

*NSF 142079 - Food Grade
**NSF142078 - Food Grade

Additional Notes:

Note: Sales tax will be added to all orders unless an exemption is on file.

Prepared by:
Globl Green Lubricants
2074 Tamarin Dr
Columbus, OH 43235
sales@globalgreenlubricants.com

Authorized by

Date